




CONTAINERIZED SEAWATER DESALINATION

Packaged Plants for Water Treatment



Seawater Desalination Plant



Raw water with a TDS of up to 40.000 ppm serves as a raw water source for the desalination plant. For prevention of accumulation, suspended solids on the membrane surface the raw water is filtered over a fine filter. This pretreatment measure guarantees that no solids interfere with the desalination process.

Reverse osmoses is a reliable technology for desalination. Therefore the required intake water quality to the reverse osmoses is essential. It is known that, most of the operation problems of an reverse osmoses system is linked with poor quality of intake water to the reverse osmoses.

It's very important to take proper pretreatment technology in order to optimize the lifetime of membrane, chemical dosing duration, operation cost, project construction space, project capital investment, and so on. Therefore, an efficient pretreatment has to be established by the client to guarantee the system running.

The desalination equipment is installed in one container, which is completely prefabricated.

Typical Analyses

| | | Feed | Product Water | WHO-Recommendations |
|-------------|-----|--------|---------------|---------------------|
| Calcium | ppm | 416 | 35,8 | - |
| Magnesium | ppm | 1326 | 10,2 | - |
| Sodium | ppm | 12623 | 96,8 | - |
| Potassium | ppm | 386 | 6,2 | - |
| Chloride | ppm | 22165 | 180 | 250 |
| Sulphate | ppm | 2939 | 13,7 | 400 |
| Nitrate | ppm | 0,9 | 0,0 | - |
| Bicarbonate | ppm | 143 | 100,3 | - |
| Iron | ppm | < 0,3 | < 0,3 | < 0,3 |
| Manganese | ppm | < 0,1 | < 0,1 | < 0,1 |
| Silica | ppm | 2,0 | 0,0 | - |
| TDS | ppm | <40000 | <300 | 500 |
| SDI (-) | | max 5 | < 1 | - |
| pH (-) | | ~8 | 7 | 6,5 - 8,5 |
| Temperature | °C | 20 | 20 | - |


Production of drinking water and water for irrigation and industrial processes.
Containerized package plants with a capacity up to 500 m³/day consisting of:

Scope of Supply

- Container-frame:** 40 ft according to ISO-standard (12,4 x 2,4 x 2,8 meter).
- Fine filters:** 100 % standby, easy handling, bag filters rating: 5-10 micron, non corrosive plastic housing.
- Pressure pump, Energy recovery:** high-efficient plunger pump with pressure exchanger.
- RO elements:** 8" spiral wound high rejection type, OEM-warranty 3 years.
- Pressure vessels:** high-quality GRP-vessel.
- Chemical dosing:** 2 complete dosing stations for acid and sodiumbisulfite including stand-by pumps.
- Cleaning unit:** complete automatic cleaning-in-place ("CIP") system.
- Remote control:** GSM-based on-line support

Options

- pH Adjustment
- Post disinfection
- Remineralization
- Data monitoring



Highlights

- Low specific water costs due to high energy efficiency: ~2,5 kWh/m³ (with energy recovery)
- Compact modular units
- Low chemical consumption
- High quality materials like GRP, seawater resistant
- stainless steel (SMO 254, 1.4539 Duplex)
- All plants are function-tested prior to dispatch to allow for quick start-up at site
- Complete installation into a 40 ft container



Acon optionally provides all required pre- and post treatments, according to your water analyses and permeate requirements.

Please contact us for further information.

Your contact:



Kevin Gesseau

Development Director

Cell: 00 27 836 05 58 62

Tel: 00 27 114 47 87 54

Email: frenchzulu@iafrica.com

No. 71, 4th Avenue, Inanda
Sandton, Gauteng, South Africa

Darius Boshoff

Technical Director

Tel: 00 27 829 68 11 30

Email: darius@energidrop.com

ACON Environment GmbH

Schubertstraße 8

A-4600 Wels

Austria - Europe

Tel. +43 (0) 7242 206 342 12

Fax +43 (0) 7242 206 342 20

www.acon-es.com

office@acon-es.com

CEO: Mag. PhDr. Peter Buchegger

Mobil +43 (0) 664 9690 110

Landesgericht Wels FN 244135y

Steuer-Nr.: 030/6941 - UID-Nr.: ATU57786257